SINUS TRAVEL 3000 24/230V WHITE (1500/3000) LCD + PILOT VOLTAGE INVERTER

REGULAR RANGE

PRODUCT CODE
3SITW300024

EAN
5904100453290

CATEGORY
Voltage inverters

SUBCATEGORY
SINUS TRAVEL voltage inverters 12/24VDC > 230VAC

PRODUCT PAGE
voltpolska.pl/produkty/przetwornica-napiecia-sinus-travel-300...



ABOUT THE PRODUCT

Compact voltage inverter VOLT POLSKA SINUS TRAVEL 3000 24/230V WHITE (1500/3000) LCD + PILOT VOLTAGE INVERTER, intended to power household consumer electronics and household appliances directly from a 24 V battery. It generates 230 V AC voltage at a frequency of 50 Hz in the form of a pure sine wave.

The device is equipped with a clear LCD display showing the input and output voltage, power, frequency, battery level and error codes. Two USB-A ports with QC fast-charging function 3.0 rated at 18 W and a USB-C PD 30 W connector enable charging of compatible devices.

Cooling is provided by an intelligent temperature-dependent fan. The inverter has protection against overload, short circuit, overheating, low and high voltage, and reverse polarity. The LCD display indication includes the OV, LV, OT, OL and S.C. codes.

TECHNICAL SPECIFICATIONS

Electrical specifications	**Continuous power (constant)**	1500 W
	Total power (instantaneous)	3000 W
	Input voltage DC	12 V / 24 V (as indicated by the name, dedicated to 24 V)
	Output voltage AC	230 V ±5%
	Output frequency	50 Hz ±0,5 Hz
	Output voltage waveform	Pure sine wave
	Efficiency	88% - 92%
Ports and connectors	**Output USB-A**	2x QC 3.0 (Fast charging 18 W)
	Output USB-C	PD 30 W

VOLT POLSKA Sp. z o.o.

ul. Świemirowska 3, 81-877 Sopot
NIP 5851458032 | REGON 221142660
KRS 0000372066

voltpolska.pl
(58) 500-85-62
hurt@voltpolska.pl
pomoc@voltpolska.pl

GENERATED: 2026-10-30 15:23

TECHNICAL SPECIFICATIONS - CONTINUED

Functions and protection	**LCD display**	Indicates: input voltage/output voltage, power, frequency, battery level, error codes
	Error codes on LCD	OV (overvoltage), LV (low voltage), OT (overheating), OL (overload), S.C. (short circuit)
	Protection	Protection against overload, short circuit, overheating (cut-off and alarm at voltage drops/rises), low/high voltage, and reverse polarity (fuse blowing)
	Cooling	Intelligent cooling fan (switching on at approx. 45°C)
	Control	ON/OFF switch, wired/wireless remote control included
Dimensions and Operating Environment	**Operating temperature**	-20°C to +50°C
	Device dimensions	390 x 205 x 145 mm
	Net weight	5,7 kg ± 2%

PRODUCT GALLERY





PRODUCT GALLERY - CONTINUED





VOLT POLSKA Sp. z o.o.

ul. Świemirowska 3, 81-877 Sopot
NIP 5851458032 | REGON 221142660
KRS 0000372066

voltpolska.pl
(58) 500-85-62
hurt@voltpolska.pl
pomoc@voltpolska.pl

This datasheet was generated automatically; technical data and images are for reference only and may change without notice. To the extent permitted by law, VOLT POLSKA accepts no liability for any errors or inaccuracies in this datasheet.