SINUS TRAVEL 4000 12/230V WHITE (2000/4000) LCD + PILOT VOLTAGE INVERTER

REGULAR RANGE

PRODUCT CODE
3SITW400012

EAN
5904100453306

CATEGORY
Voltage inverters

SUBCATEGORY
SINUS TRAVEL 12/24VDC > 230VAC voltage inverters

PRODUCT PAGE
voltpolska.pl/produkty/przetwornica-napiecia-sinus-travel-400...



ABOUT THE PRODUCT

The SINUS TRAVEL 4000 12/230V WHITE (2000/4000) LCD + PILOT voltage inverter, index 3SITW400012, is designed to convert DC DC voltage into AC 230 V AC voltage. It generates a pure sine-wave voltage suitable for powering devices requiring a stable energy source.

The device is equipped with a LCD display showing the input and output voltage, power, frequency, battery level and error codes: OV, LV, OT, OL and S.C. It also features USB-A outputs with QC fast-charging function 3.0 18 W and USB-C PD 30 W.

The inverter is protected against overload, short circuit, overheating, low and high voltage, and reverse polarity. In W the event of overheating, shutdown and an alarm are activated, while reverse-polarity protection operates by blowing the fuse.

TECHNICAL SPECIFICATIONS

Electrical specifications	**Continuous power (constant)**	2000 W
	Total power (instantaneous)	4000 W
	Input voltage DC	12 V / 24 V
	Output voltage AC	230 V ±5%
	Output frequency	50 Hz ±0,5 Hz
	Output voltage waveform	Pure sine wave
	Efficiency	88% - 92%
Ports and Connectors	**Output USB-A**	2x QC 3.0 (Fast charging 18 W)
	Output USB-C	PD 30 W

VOLT POLSKA Sp. z o.o.

ul. Świemirowska 3, 81-877 Sopot
NIP 5851458032 | REGON 221142660
KRS 0000372066

voltpolska.pl
(58) 500-85-62
hurt@voltpolska.pl
pomoc@voltpolska.pl

GENERATED: 2026-10-30 16:11

TECHNICAL SPECIFICATIONS - CONTINUED

Functions and Protections	**Display LCD**	Indicates: input /output voltage, power, frequency, battery level, error codes
	Error codes on LCD	OV (overvoltage), LV (low voltage), OT (overheating), OL (overload), S.C. (short circuit)
	Protection	Protection against overload, short circuit, overheating (shutdown and alarm), low/high voltage and reverse polarity (fuse blown)
	Cooling	Intelligent fan that switches on at approx. 45°C
	Controls	ON/OFF switch and the option to connect a remote control
Overall Dimensions and Operating Environment	**Operating temperature**	-20°C to +50°C
	Device dimensions	355 x 247 x 95 mm
	Net weight	4,48 kg ± 2%

PRODUCT GALLERY





VOLT POLSKA Sp. z o.o.

ul. Świemirowska 3, 81-877 Sopot
NIP 5851458032 | REGON 221142660
KRS 0000372066

voltpolska.pl
(58) 500-85-62
hurt@voltpolska.pl
pomoc@voltpolska.pl

PRODUCT GALLERY - CONTINUED





VOLT POLSKA Sp. z o.o.

ul. Świemirowska 3, 81-877 Sopot
NIP 5851458032 | REGON 221142660
KRS 0000372066

voltpolska.pl
(58) 500-85-62
hurt@voltpolska.pl
pomoc@voltpolska.pl

This datasheet was generated automatically; technical data and images are for reference only and may change without notice. To the extent permitted by law, VOLT POLSKA accepts no liability for any errors or inaccuracies in this datasheet.