SINUS TRAVEL 4000 24/230V WHITE (2000/4000) LCD + PILOT VOLTAGE INVERTER

REGULAR RANGE

PRODUCT CODE
3SITW400024

EAN
5904100453313

CATEGORY
Voltage inverters

SUBCATEGORY
SINUS TRAVEL 12/24VDC > 230VAC voltage inverters

PRODUCT PAGE
voltpolska.pl/produkty/przetwornica-napiecia-sinus-travel-400...



ABOUT THE PRODUCT

SINUS TRAVEL 4000 24/230V WHITE (2000/4000) LCD + PILOT voltage inverter by VOLT POLSKA is a compact device designed to power a wide range of household consumer electronics and home appliances directly from a dedicated battery.

The model generates AC 230 V AC voltage at a frequency of 50 Hz in the form of a pure sine wave. It is equipped with a clear LCD display showing the input and output voltage, power, frequency, battery level and error codes.

The inverter features an intelligent temperature-dependent cooling fan and protection against overload, short circuit, overheating, low and high voltage, and reverse polarity. Two USB-A QC 3.0 ports with a power rating of 18 W and a USB-C PD 30 W connector are available.

TECHNICAL SPECIFICATIONS

Electrical specifications	**Continuous power (constant)**	2000 W
	Total power (momentary)	4000 W
	Input voltage DC	12 V / 24 V (optimised for 24 V as indicated by the name)
	Output voltage AC	230 V ±5%
	Output frequency	50 Hz ±0,5 Hz
	Output voltage waveform	Pure sine wave
	Efficiency	88% - 92%
Ports and Connectors	**Output USB-A**	2x QC 3.0 (Quick Charge 18 W)
	Output USB-C	PD 30 W

VOLT POLSKA Sp. z o.o.

ul. Świemirowska 3, 81-877 Sopot
NIP 5851458032 | REGON 221142660
KRS 0000372066

voltpolska.pl
(58) 500-85-62
hurt@voltpolska.pl
pomoc@voltpolska.pl

GENERATED: 2026-10-30 16:11

TECHNICAL SPECIFICATIONS - CONTINUED

Functions and Protections	**LCD display**	Indicates: input /output voltage, power, frequency, battery level, error codes
	Error codes on LCD	OV (overvoltage), LV (low voltage), OT (overheating), OL (overload), S.C. (short circuit)
	Protection	Protection against overload, short circuit, overheating (shutdown and alarm during drops/rises), low/high voltage, and reverse polarity (fuse blowout)
	Cooling	Intelligent cooling fan (activating at approx. 45°C)
	Control	ON/OFF switch, remote control included
Dimensions and Operating Environment	**Operating temperature**	-20°C to +50°C
	Device dimensions	355 x 247 x 95 mm
	Net weight	4,42 kg - 4,48 kg ± 2%

PRODUCT GALLERY





PRODUCT GALLERY - CONTINUED





VOLT POLSKA Sp. z o.o.

ul. Świemirowska 3, 81-877 Sopot
NIP 5851458032 | REGON 221142660
KRS 0000372066

voltpolska.pl
(58) 500-85-62
hurt@voltpolska.pl
pomoc@voltpolska.pl

This datasheet was generated automatically; technical data and images are for reference only and may change without notice. To the extent permitted by law, VOLT POLSKA accepts no liability for any errors or inaccuracies in this datasheet.