POWER SINUS 1500 12/230V (1500W/4500VA) EMERGENCY POWER SUPPLY

REGULAR RANGE

PRODUCT CODE
3SSP150012

EAN
5904100450008

CATEGORY
Emergency power supply

SUBCATEGORY
POWER SINUS emergency power supplies (high-power)

PRODUCT PAGE
voltpolska.pl/produkty/power-sinus-1500-12-230v-1500-3000...



ABOUT THE PRODUCT

Power Sinus 1500 12/230V (1500W/4500VA) is an emergency power supply combining the functions of an inverter, charger and automatic AC transfer switch. The device operates as a UPS power supply with a Pure Sine Wave voltage waveform, providing stable voltage and high starting current.

The power supply is designed to operate with various types of batteries with a voltage of 12V. It can power, among other things, refrigerators, freezers, compressors and air compressors, motorhomes, pumps and central-heating boilers, gates and solar systems. Thanks to the sinusoidal output voltage waveform, it is also suitable for inductive devices such as power tools, air conditioners, refrigerators and freezers.

The device is equipped with overload, thermal, undervoltage and short-circuit protection, as well as battery overcharge protection. The maximum transfer time between the mains and the battery is 10 ms.

TECHNICAL SPECIFICATIONS

General Parameters	**Continuous power**	1500W
	Total power (peak)	4500VA
	Power factor	0.8 - 1.0 cos φ
	Efficiency	Up to 88% (in inverter mode) / >95% (in mains mode)
	Mains/battery transfer time	10 ms (max)
Input Parameters (Mains)	**Input voltage range (mains)**	184 - 254 VAC (Narrow mode - SW2 pos. 0) / 140 - 270 VAC (Wide mode - SW2 pos. 1)
	Input frequency range	Narrow: 47-55 Hz / Wide: 43-55 Hz

VOLT POLSKA Sp. z o.o.

ul. Świemirowska 3, 81-877 Sopot
NIP 5851458032 | REGON 221142660
KRS 0000372066

voltpolska.pl
(58) 500-85-62
hurt@voltpolska.pl
pomoc@voltpolska.pl

GENERATED: 2026-11-10 14:57

TECHNICAL SPECIFICATIONS - CONTINUED

Output Parameters (AC)	**Output voltage**	230V
	Output voltage frequency	50 ± 0,3Hz
	Output voltage waveform	Pure sine wave
	Harmonic distortion (THD)	< 10%
Battery and Charging	**Battery voltage**	12 VDC
	Input voltage range (battery)	10,5V - 15V ± 0,5VDC
	Max. charging current	45 ± 5A
	Supported battery types (charging modes)	1. Gel U.S.A. — 14.0V / 13.7V
Bypass and Protections	**Input voltage waveform**	Sine wave (mains or generator)
	Undervoltage cutoff	184V / 154V ±4%
	Undervoltage activation	194V / 164V ±4%
	Overvoltage cutoff	253V ±4%
	Overvoltage activation	243V ±4%
	Protection	Short-circuit protection (with current limiter function after 1s), overcharge, overvoltage and undervoltage protection
General Data and Installation	**Operating temperature**	from -20°C to 40°C; (above 40°C, the load must be reduced; maximum temperature 50°C)
	Humidity	< 95%, non-condensing
	Mounting	Wall-mounted or horizontal installation
	Device dimensions	326.3 x 176.8 x 136.2 mm
	Net weight	12 kg ±3%
	Individual package dimensions	475 x 230 x 205 mm
	Unit packaging weight	13 kg ±3%

VOLT POLSKA Sp. z o.o.

ul. Świemirowska 3, 81-877 Sopot

NIP 5851458032 | REGON 221142660

KRS 0000372066

voltpolska.pl

(58) 500-85-62

hurt@voltpolska.pl

pomoc@voltpolska.pl


PRODUCT GALLERY











VOLT POLSKA Sp. z o.o.

ul. Świemirowska 3, 81-877 Sopot

NIP 5851458032 | REGON 221142660

KRS 0000372066

voltpolska.pl

(58) 500-85-62

hurt@voltpolska.pl

pomoc@voltpolska.pl

This datasheet was generated automatically; technical data and images are for reference only and may change without notice. To the extent permitted by law, VOLT POLSKA accepts no liability for any errors or inaccuracies in this datasheet.