COMFORT HT-08 FLOOR THERMOSTAT + SMARTPHONE APPLICATION (Wi-Fi)

REGULAR RANGE

PRODUCT CODE
3ZTERHT080

EAN
5903293765944

CATEGORY
Home and garden

SUBCATEGORY
COMFORT room thermostats (wired and wireless)

PRODUCT PAGE
voltpolska.pl/produkty/comfort-ht-08-przewodowy-wi-fi-termo...



ABOUT THE PRODUCT

The COMFORT floor thermostat HT-08 is used to switch domestic heating systems on and off. It enables manual control or operation according to programmable cycles, maintaining a comfort or economy temperature in accordance with the set programme and time. It reduces energy costs by lowering the temperature when users are absent.

The device is equipped with two temperature sensors: a built-in sensor intended to measure room temperature and an external sensor used to regulate floor temperature. The thermostat is connected by wire to the central heating boiler, while Wi-Fi communication enables control via a smartphone using the Smart Life application.

HT-08 offers two operating modes: manual and PRG, programming 4 cycles for each day, and displaying the current and set temperatures. The large, clear display with white backlight, compact dimensions, electronic heating control and temperature protection against device overheating ensure convenient operation.

The open-window mode (OWD) automatically switches off heating when a sudden temperature drop is detected, by default by 2°C within 15 minutes. The device returns to normal mode after 30 minutes, while pressing any button deactivates the function immediately.

TECHNICAL SPECIFICATIONS

Electrical specifications	**Power supply**	230 V, 50/60 Hz
	Maximum load	16 A
	Temperature sensor	NTC 10K (supports air and floor sensors)

VOLT POLSKA Sp. z o.o.

ul. Świemirowska 3, 81-877 Sopot
NIP 5851458032 | REGON 221142660
KRS 0000372066

voltpolska.pl
(58) 500-85-62
hurt@voltpolska.pl
pomoc@voltpolska.pl

GENERATED: 2026-10-30 16:06

TECHNICAL SPECIFICATIONS - CONTINUED

Operating features and construction	**Thermostat type**	Wired with Wi-Fi communication (controlled via the Smart Life application)
	Temperature setting range	5°C to 35°C
	Operating temperature range	0°C to 50°C
	Sensitivity (measurement accuracy)	± 0,5°C
	Permissible relative humidity	85%
	Programming options	7 days (weekly), 4 cycles per day
	Display and backlight	Black with white backlight
	Housing material	ABS UL94-5 (flame-retardant)
	IP rating	IP30
	Certifications	CE, RoHS, RED
Dimensions and logistics	**Thermostat dimensions**	86 x 86 x 16,8 mm
	Net weight	0,144 kg
	Individual package dimensions	90 x 90 x 80 mm
	Individual package weight	0,25 kg

PRODUCT GALLERY






VOLT POLSKA Sp. z o.o.

ul. Świemirowska 3, 81-877 Sopot
NIP 5851458032 | REGON 221142660
KRS 0000372066

voltpolska.pl
(58) 500-85-62
hurt@voltpolska.pl
pomoc@voltpolska.pl

PRODUCT GALLERY - CONTINUED





VOLT POLSKA Sp. z o.o.

ul. Świemirowska 3, 81-877 Sopot

NIP 5851458032 | REGON 221142660

KRS 0000372066

voltpolska.pl

(58) 500-85-62

hurt@voltpolska.pl

pomoc@voltpolska.pl

This datasheet was generated automatically; technical data and images are for reference only and may change without notice. To the extent permitted by law, VOLT POLSKA accepts no liability for any errors or inaccuracies in this datasheet.