MICROUPS 650VA/360W 1×7Ah BACKUP POWER SUPPLY [TOWER]

REGULAR RANGE

PRODUCT CODE
5UP0600070

EAN
5903111886820

CATEGORY
Backup power supply

SUBCATEGORY
MICRO UPS backup power supplies (computer UPS units with battery)

PRODUCT PAGE
voltpolska.pl/produkty/micro-ups-650-7ah-360-650w-kompute...



ABOUT THE PRODUCT

Micro UPS 650 7Ah is a Line-Interactive backup power supply designed to power computers and peripheral devices. Its compact enclosure and low weight are suitable for small office rooms. The built-in AVR voltage stabiliser protects connected devices against sudden voltage fluctuations, while the battery start function enables operation without a direct connection to the mains.

The device is equipped with a microprocessor-based control system, an automatic energy-saving function, overload protection and a AGM 1×7Ah battery. Two 230V power sockets allow two devices to be supported simultaneously. The power supply can operate with the free ViewPower software, enabling monitoring and configuration of operating parameters, messages and alarms.

Micro UPS 650 7Ah can power, among other things, computers, laptops, small servers, workstations, network and peripheral devices, consumer electronics, alarm and CCTV systems, telecommunications and fiscal devices, and control-measurement equipment. It is also equipped with protection against low and high voltage, short circuits, overload and overheating.

W in mains mode, the power supply supports the full load 100%. During backup operation from the battery, the recommended load is 50–75% of the rated power. Connecting devices with full power 100% in battery mode will cause immediate shutdown UPS-a.

TECHNICAL SPECIFICATIONS

General Parameters	**Continuous power**	360W
	Total power (instantaneous)	650VA
	Efficiency	~ 90%
	Mains/battery transfer time	~ 3 ms
Input Parameters (Mains)	**Input voltage**	230 VAC (50/60Hz)
	Input voltage range	150 - 290 VAC +- 3%

VOLT POLSKA Sp. z o.o.

ul. Świemirowska 3, 81-877 Sopot
NIP 5851458032 | REGON 221142660
KRS 0000372066

voltpolska.pl
(58) 500-85-62
hurt@voltpolska.pl
pomoc@voltpolska.pl

GENERATED: 2026-10-30 16:02

TECHNICAL SPECIFICATIONS - CONTINUED

Output Parameters (AC)	**Frequency**	50/60 Hz +- 1Hz
	Voltage waveform	Approximated sine wave
	Output voltage range	with AVR - 210 - 248 VAC +- 3%
Battery and Charging	**Type / Capacity**	12V / 7Ah x 1
	Charging time	6-8 hours to 90%
Indicators and Alarms	**AC mode (mains)**	The AC MODE icon lights up on the display
	DC mode (battery)	The BATT. MODE icon lights up on the display
	Fault mode	The FAULT icon lights up on the display
	Alarm: Backup mode	Signal every 10 s
	Alarm: Low battery charge	Signal every 1 s
	Alarm: Overload	Signal every 0,5 s
	Alarm: Error	Continuous signal
Protection and Operating Environment	**Comprehensive protection**	Overload, overcharge and discharge protection
	Operating temperature	0 - 40 C
	Noise level	< 40 dB
General Data and Installation	**Device dimensions**	297 x 101 x 142 mm
	Net weight	4,2 kg
	Individual package dimensions	340 x 140 x 220 mm
	Individual package weight	4,5 kg

VOLT POLSKA Sp. z o.o.

ul. Świemirowska 3, 81-877 Sopot

NIP 5851458032 | REGON 221142660

KRS 0000372066

voltpolska.pl

(58) 500-85-62

hurt@voltpolska.pl

pomoc@voltpolska.pl

PRODUCT GALLERY









VOLT POLSKA Sp. z o.o.

ul. Świemirowska 3, 81-877 Sopot
NIP 5851458032 | REGON 221142660
KRS 0000372066

voltpolska.pl
(58) 500-85-62
hurt@voltpolska.pl
pomoc@voltpolska.pl

PRODUCT GALLERY - CONTINUED



VOLT POLSKA Sp. z o.o.

ul. Świemirowska 3, 81-877 Sopot
NIP 5851458032 | REGON 221142660
KRS 0000372066

voltpolska.pl
(58) 500-85-62
hurt@voltpolska.pl
pomoc@voltpolska.pl

This datasheet was generated automatically; technical data and images are for reference only and may change without notice. To the extent permitted by law, VOLT POLSKA accepts no liability for any errors or inaccuracies in this datasheet.