MICROUPS 1000VA/600W 1×9Ah UNINTERRUPTIBLE POWER SUPPLY [TOWER]

REGULAR RANGE

PRODUCT CODE
5UP1000028

EAN
5903111886844

CATEGORY
Uninterruptible power supply

SUBCATEGORY
MICRO UPS uninterruptible power supplies (computer UPS units with battery)

PRODUCT PAGE
voltpolska.pl/produkty/micro-ups-1000-9ah-600-1000w-kompu...



ABOUT THE PRODUCT

Micro UPS 1000 9Ah (600/1000W) is an uninterruptible power supply designed for computers and peripheral devices. Its compact enclosure and low weight make it suitable for small office spaces. The device uses Line-Interactive technology and is equipped with an AVR voltage stabiliser that protects connected devices against sudden voltage spikes.

The UPS can be started from the built-in battery without direct connection to the AC mains. It offers two 230V power sockets, overload protection and a AGM 1x9Ah battery. In W mains mode, it supports the full load (100%), while during battery backup operation the recommended load is 50-75% of the rated power. Connecting devices with full power (100%) in battery mode will cause the UPS-a to switch off immediately.

Micro UPS 1000 9Ah can power computers, laptops, small servers, workstations, network devices and peripherals, as well as consumer electronics devices, alarm and CCTV systems, telecommunications and fiscal devices, and control-measurement equipment.

The UPS works with the free ViewPower software, enabling connection to a computer via USB, monitoring and modification of operating parameters, configuration of messages and setting of alarms. Protection against low and high voltage, short circuits, overloads and overheating supports safe operation of the device. The latest software is available at: https://voltpolska.pl/soft_ups.zip

TECHNICAL SPECIFICATIONS

General Parameters	**Continuous power**	600W
	Total power (short-term)	1000VA
	Efficiency	~ 90%
	Mains/battery transfer time	~ 3 ms
Input Parameters (Mains)	**Input voltage**	230 VAC (50/60 Hz)
	Input voltage range	150 - 290 VAC +- 3%

VOLT POLSKA Sp. z o.o.

ul. Świemirowska 3, 81-877 Sopot
NIP 5851458032 | REGON 221142660
KRS 0000372066

voltpolska.pl
(58) 500-85-62
hurt@voltpolska.pl
pomoc@voltpolska.pl

GENERATED: 2026-10-30 16:02

TECHNICAL SPECIFICATIONS - CONTINUED

Output Parameters (AC)	**Frequency**	50/60 Hz +- 1Hz
	Voltage waveform	Approximated sine wave
	Output voltage range	with AVR - 210 - 248 VAC +- 3%
Battery and Charging	**Type / Capacity**	12V / 9Ah x 1 (9Ah)
	Charging time	6-8 hours to 90%
Indicators and Alarms	**AC mode (mains)**	The AC MODE icon illuminates on the display
	DC mode (battery-powered)	The BATT. MODE icon lights up on the display
	Fault mode	The FAULT icon lights up on the display
	Alarm: Backup mode	Signal every 10 s
	Alarm: Low battery charge	Signal every 1 s
	Alarm: Overload	Signal every 0,5 s
	Alarm: Error	Continuous signal
Protection and Operating Environment	**Full protection**	Overload, overcharge and deep-discharge protection
	Operating temperature	0 - 40 C
	Noise level	< 40 dB
General Data and Installation	**Device dimensions**	297 x 101 x 142 mm
	Net weight	4,9 kg
	Individual package dimensions	340 x 140 x 220 mm
	Individual package weight	4,65 kg

VOLT POLSKA Sp. z o.o.

ul. Świemirowska 3, 81-877 Sopot

NIP 5851458032 | REGON 221142660

KRS 0000372066

voltpolska.pl

(58) 500-85-62

hurt@voltpolska.pl

pomoc@voltpolska.pl

PRODUCT GALLERY













VOLT POLSKA Sp. z o.o.

ul. Świemirowska 3, 81-877 Sopot
NIP 5851458032 | REGON 221142660
KRS 0000372066

voltpolska.pl
(58) 500-85-62
hurt@voltpolska.pl
pomoc@voltpolska.pl

This datasheet was generated automatically; technical data and images are for reference only and may change without notice. To the extent permitted by law, VOLT POLSKA accepts no liability for any errors or inaccuracies in this datasheet.