MICROUPS 1500VA/900W 2×9Ah UNINTERRUPTIBLE POWER SUPPLY [TOWER]

REGULAR RANGE

PRODUCT CODE
5UP1500029

EAN
5903111886868

CATEGORY
Uninterruptible power supply

SUBCATEGORY
MICRO UPS uninterruptible power supplies (computer UPS with battery)

PRODUCT PAGE
voltpolska.pl/produkty/micro-ups-1500-2x9ah-900-1500w-kom...



ABOUT THE PRODUCT

MICROUPS 1500VA/900W 2×9Ah UNINTERRUPTIBLE POWER SUPPLY [TOWER] is a Line-Interactive uninterruptible power supply designed to protect computers, peripheral devices, small servers, workstations, network devices, consumer electronics, alarm systems and CCTV, telecommunications equipment, and control-measurement equipment.

The device is equipped with a microprocessor-based control system, an AVR voltage stabiliser, and protection against low and high voltage, short circuits, overloads, and overheating. The built-in automatic energy-saving function reduces energy consumption, while the compact enclosure and low weight facilitate use in small office spaces.

The power supply has three 230V sockets, enabling three devices to be supplied simultaneously, and a AGM 2x9Ah battery. It can be started without being directly connected to the AC mains. In W mains mode, it supports the full 100% load, while the recommended load in battery mode is 50-75% of the rated power. Connecting devices with the full 100% power in battery mode will immediately switch off the UPS-a.

The device works with the free ViewPower software, enabling connection to a computer via USB, monitoring and changing operating parameters, configuring messages, and setting alarms. Current control and parameter monitoring are available at: https://voltpolska.pl/soft_ups.zip

TECHNICAL SPECIFICATIONS

General parameters	**Continuous power**	900W
	Total power (instantaneous)	1500VA
	Efficiency	~ 90%
	Mains/battery transfer time	~ 3 ms
Input parameters (mains)	**Input voltage**	230 VAC (50/60Hz)
	Input voltage range	150 - 290 VAC +- 3%

VOLT POLSKA Sp. z o.o.

ul. Świemirowska 3, 81-877 Sopot
NIP 5851458032 | REGON 221142660
KRS 0000372066

voltpolska.pl
(58) 500-85-62
hurt@voltpolska.pl
pomoc@voltpolska.pl

GENERATED: 2026-10-30 15:17

TECHNICAL SPECIFICATIONS - CONTINUED

Output parameters (AC)	**Frequency**	50/60 Hz +- 1Hz
	Voltage waveform	Approximated sine wave
	Output voltage range	with AVR - 210 - 248 VAC +- 3%
Battery and charging	**Type / Capacity**	2x9Ah
	Charging time	6-8 hours to 90%
Indicators and Alarms	**AC mode (mains)**	The AC MODE icon is illuminated on the display
	DC mode (battery)	The BATT. MODE icon illuminates on the display
	Fault mode	The FAULT icon illuminates on the display
	Alarm: Backup mode	Signal every 10 s
	Alarm: Low battery charge	Signal every 1 s
	Alarm: Overload	Signal every 0,5 s
	Alarm: Error	Continuous signal
Protection and Operating Environment	**Full protection**	Overload, overcharge and deep-discharge protection
	Operating temperature	0 - 40 C
	Noise level	< 40 dB
General Data and Installation	**Device dimensions**	370 x 135 x 165 mm
	Net weight	10 kg
	Individual package dimensions	470 x 195 x 255 mm
	Individual package weight	10,3 kg

VOLT POLSKA Sp. z o.o.

ul. Świemirowska 3, 81-877 Sopot

NIP 5851458032 | REGON 221142660

KRS 0000372066

voltpolska.pl

(58) 500-85-62

hurt@voltpolska.pl

pomoc@voltpolska.pl

PRODUCT GALLERY













PRODUCT GALLERY - CONTINUED



VOLT POLSKA Sp. z o.o.

ul. Świemirowska 3, 81-877 Sopot
NIP 5851458032 | REGON 221142660
KRS 0000372066

voltpolska.pl
(58) 500-85-62
hurt@voltpolska.pl
pomoc@voltpolska.pl

This datasheet was generated automatically; technical data and images are for reference only and may change without notice. To the extent permitted by law, VOLT POLSKA accepts no liability for any errors or inaccuracies in this datasheet.