MICROUPS 3000VA/1800W 4×9Ah UNINTERRUPTIBLE POWER SUPPLY [TOWER]

REGULAR RANGE



PRODUCT CODE
5UP3000049

EAN
5903111886905

CATEGORY
Uninterruptible power supply

SUBCATEGORY
MICRO UPS uninterruptible power supplies (computer UPS units with battery)

PRODUCT PAGE
voltpolska.pl/produkty/micro-ups-3000-4x9ah-1800-3000w-ko...

ABOUT THE PRODUCT

Micro UPS 3000 4x9Ah (1800/3000W) is an uninterruptible power supply designed for computers and peripheral devices. Its compact enclosure and low weight make the unit suitable for use in small office spaces. The built-in AVR voltage stabiliser protects connected devices against sudden changes in mains voltage.

The UPS is manufactured using Line-Interactive technology and is equipped with a microprocessor-based control system, a AGM 4x9Ah battery and two 230V sockets, enabling two devices to be supported simultaneously. It can be started without a direct connection to the AC mains. An automatic energy-saving function and overload protection are also available.

Micro UPS 3000 4x9Ah can power, among other things, computers, laptops, small servers, workstations, network and peripheral devices, consumer electronics equipment, alarm and CCTV systems, telecommunications and fiscal devices, and control-measurement equipment.

The unit is compatible with the free ViewPower software, which enables connection via USB, monitoring and adjustment of operating parameters, configuration of messages and setting of alarms. The UPS protects connected devices and its own circuits against low and high voltage, short circuits, overload and overheating. In W mains mode, it supports the full load, whereas during battery operation the recommended load is 50-75% of the rated power.

TECHNICAL SPECIFICATIONS

General Parameters	**Continuous power**	1800W
	Total power (peak)	3000VA
	Efficiency	~ 90%
	Mains/battery transfer time	~ 3 ms
Input Parameters (Mains)	**Input voltage**	170 - 280 VAC
	Input voltage range	170 - 280 VAC

VOLT POLSKA Sp. z o.o.

ul. Świemirowska 3, 81-877 Sopot
NIP 5851458032 | REGON 221142660
KRS 0000372066

voltpolska.pl
(58) 500-85-62
hurt@voltpolska.pl
pomoc@voltpolska.pl

GENERATED: 2026-10-30 16:03

TECHNICAL SPECIFICATIONS - CONTINUED

Output Parameters (AC)	**Frequency**	50/60 Hz +- 1Hz
	Voltage waveform	Approximated sine wave
	Output voltage range	with AVR - 210 - 248 VAC +- 3%
Battery and Charging	**Type / Capacity**	4x9Ah (24VDC)
	Charging time	6-8 hours to 90%
Indicators and Alarms	**AC mode (mains)**	The AC MODE icon illuminates on the display
	DC mode (battery)	The BATT. MODE icon illuminates on the display
	Fault mode	The FAULT icon illuminates on the display
	Alarm: Backup mode	Signal every 10 s
	Alarm: Low battery charge	Signal every 1 s
	Alarm: Overload	Signal every 0,5 s
	Alarm: Error	Continuous signal
Protection and Operating Environment	**Full protection**	Overload, overcharge and over-discharge protection
	Operating temperature	0 - 40 C
	Noise level	< 40 dB
General Data and Installation	**Device dimensions**	466 x 138 x 166 mm
	Net weight	19 kg
	Individual package dimensions	550 x 195 x 155 mm
	Individual package weight	19,5 kg

PRODUCT GALLERY













VOLT POLSKA Sp. z o.o.

ul. Świemirowska 3, 81-877 Sopot
NIP 5851458032 | REGON 221142660
KRS 0000372066

voltpolska.pl
(58) 500-85-62
hurt@voltpolska.pl
pomoc@voltpolska.pl

PRODUCT GALLERY - CONTINUED



VOLT POLSKA Sp. z o.o.

ul. Świemirowska 3, 81-877 Sopot
NIP 5851458032 | REGON 221142660
KRS 0000372066

voltpolska.pl
(58) 500-85-62
hurt@voltpolska.pl
pomoc@voltpolska.pl

This datasheet was generated automatically; technical data and images are for reference only and may change without notice. To the extent permitted by law, VOLT POLSKA accepts no liability for any errors or inaccuracies in this datasheet.