RACKUPS 1200VA/720W 2×7Ah UNINTERRUPTIBLE POWER SUPPLY [RACK]

REGULAR RANGE

PRODUCT CODE
5UTRA91227

EAN
5903111886936



CATEGORY
Uninterruptible power supply

SUBCATEGORY
RACK uninterruptible power supplies UPS (computer power supplies with battery)

PRODUCT PAGE
voltpolska.pl/produkty/rackups-1200va720w-27ah-zasilacz-aw...

ABOUT THE PRODUCT

RACKUPS 1200VA/720W 2×7Ah UNINTERRUPTIBLE POWER SUPPLY [RACK] is a device for uninterrupted power supply to computers, network devices and other equipment requiring operational continuity. It is designed for installation in telecommunications cabinets in the RACK 19" 2U standard, making it suitable for small and medium-sized server cabinets.

The power supply uses Line-Interactive technology and an AVR module, which stabilises the mains voltage and limits the impact of sudden voltage surges on connected devices. The microprocessor-based control system ensures rapid switching to battery mode in the event of a power failure. The cold-start function enables the device to be started without a direct connection to the mains AC.

The model is equipped with a maintenance-free AGM 12V / 7Ah x 2 battery and a clear LCD display for monitoring the most important parameters. Two 230V power sockets enable two devices to be powered simultaneously, while three 230V computer sockets allow additional equipment to be connected.

TECHNICAL SPECIFICATIONS

General Parameters	**Continuous power**	720W
	Total power (instantaneous)	1200VA
	Transfer time	Average 2-6ms, max 10ms
Input Parameters (Mains)	**Input voltage**	230 VAC
	Input voltage range	140 - 300 VAC
Output Parameters (AC)	**Output voltage tolerance**	± 10%
	Voltage waveform	Approximated sine wave

VOLT POLSKA Sp. z o.o.

ul. Świemirowska 3, 81-877 Sopot
NIP 5851458032 | REGON 221142660
KRS 0000372066

voltpolska.pl
(58) 500-85-62
hurt@voltpolska.pl
pomoc@voltpolska.pl

TECHNICAL SPECIFICATIONS - CONTINUED

Battery and Charging	**Type and number of batteries**	12V / 7Ah x 2
	Charging time	6 hours of charging to 90% of nominal capacity
Operating environment	**Humidity / temperature**	0-90% RH / 0 - 40°C
	Generated noise	< 40 dB
General Data and Installation	**Device dimensions**	310 x 438 x 87 mm ±1-2mm (standard RACK 19" 2U)
	Net weight	10,8 kg
	Individual package dimensions	495 x 395 x 202 mm
	Individual package weight	11,25 kg

PRODUCT GALLERY





VOLT POLSKA Sp. z o.o.

ul. Świemirowska 3, 81-877 Sopot
NIP 5851458032 | REGON 221142660
KRS 0000372066

voltpolska.pl
(58) 500-85-62
hurt@voltpolska.pl
pomoc@voltpolska.pl

PRODUCT GALLERY - CONTINUED









VOLT POLSKA Sp. z o.o.

ul. Świemirowska 3, 81-877 Sopot

NIP 5851458032 | REGON 221142660

KRS 0000372066

voltpolska.pl

(58) 500-85-62

hurt@voltpolska.pl

pomoc@voltpolska.pl

This datasheet was generated automatically; technical data and images are for reference only and may change without notice. To the extent permitted by law, VOLT POLSKA accepts no liability for any errors or inaccuracies in this datasheet.