12V / 24V 8A AUTOMATIC BATTERY CHARGER

DISCONTINUED

PRODUCT CODE
6PRO122408

EAN
5903111886585

CATEGORY
Battery chargers and accessories

SUBCATEGORY
Automatic battery chargers AGM

PRODUCT PAGE
voltpolska.pl/produkty/prostownik-akumulatorowy-12-24v-8a...



ABOUT THE PRODUCT

Automatic battery charger 12/24V 8A designed for charging lead-acid batteries with liquid electrolyte and lead--acid VRLA automotive batteries, including AGM and GEL. Suitable for batteries used in cars, motorcycles, scooters and garden equipment.

The device offers automatic charging, diagnostics, voltage maintenance and battery conditioning modes. It enables charging deeply discharged batteries and operation in power generator mode 13,6V/4A.

Electronic protections prevent reverse polarity, sparking, overheating and short circuits, as well as battery overcharging. The charger is also equipped with absorption, conditioning, power supply and BOOST modes.

TECHNICAL SPECIFICATIONS

Electrical and Charging Parameters	**Charging current**	8 A (for 12V) / 4 A (for 24V)
	Input voltage	200 - 260 V AC
	Output voltage	12 V / 24 V (automatic selection)
	Voltage frequency	50/60 Hz
	Maximum output power	190 W
Functions and Operating Modes	**Battery types**	Lead--acid automotive batteries, VRLA (AGM, GEL), liquid electrolyte, MF
	Special modes	Diagnostic and recovery mode (from 4,5V for 12V / from 16V for 24V), absorption mode, conditioning mode, power supply mode 13,6V / 4A, BOOST mode 16V / 1.5A
	Protection	Electronic protection against errors (reverse polarity, sparking, temperature, short circuit)

VOLT POLSKA Sp. z o.o.

ul. Świemirowska 3, 81-877 Sopot
NIP 5851458032 | REGON 221142660
KRS 0000372066

voltpolska.pl
(58) 500-85-62
hurt@voltpolska.pl
pomoc@voltpolska.pl

GENERATED: 2026-10-30 16:10

TECHNICAL SPECIFICATIONS - CONTINUED

Dimensions and Operating Environment	**Protection class**	IP 65
	Ambient temperature	-10°C to +40°C
	Device dimensions	23,56 x 7,78 x 5,36 cm
	Net weight	746,5 g
	Single-unit packaging dimensions	9 x 8 x 27,5 cm
	Single-unit packaging weight	834,5 g

PRODUCT GALLERY





VOLT POLSKA Sp. z o.o.

ul. Świemirowska 3, 81-877 Sopot
NIP 5851458032 | REGON 221142660
KRS 0000372066

voltpolska.pl
(58) 500-85-62
hurt@voltpolska.pl
pomoc@voltpolska.pl

PRODUCT GALLERY - CONTINUED



VOLT POLSKA Sp. z o.o.

ul. Świemirowska 3, 81-877 Sopot

NIP 5851458032 | REGON 221142660

KRS 0000372066

voltpolska.pl

(58) 500-85-62

hurt@voltpolska.pl

pomoc@voltpolska.pl

This datasheet was generated automatically; technical data and images are for reference only and may change without notice. To the extent permitted by law, VOLT POLSKA accepts no liability for any errors or inaccuracies in this datasheet.